

Rotowash Classic

The standard models including loop handle, non-electrical water dosage and distribution of the cleaning solution between the brushes.

- A Universal safety handle for left and right hand operation
- B Easy grip water release control
- C Pivoting quick release cable holder
- D 10m mains cable
- E Removeable slim line clean water tank 7ltr
- H Waste water tray lid with water level indicator
- I Clean water tray
- K Bowden controlled water distribution
- M Brush pressure control knob
- N Spring loaded clip for quick removal of handle
- O Ball valve controlled water flow
- P Heavy duty side and front protector bumpers
- R Easy to fit and remove brush axes
- S Built-in brush location plate for simple and fast fitting of brushes
- T Retractable transport rollers suspend load on brushes while not in operation
- U Cylindrical brushes, easy to remove without using any tools. Available in multiple colours for hygiene control
- V Easily removable waste water tray
- W Safety thermal cut-out control
- X Specially coated aluminium body housing for high mechanical resistance



Optional Accessories



Corner Brush

Clean tight corners easily. Detaches when not needed.



Side Brush

Designed to reach the edges of all floors.



Universal Rotocart

Move the Rotowash to any location easily. Fits all machine models.

Rotowash Classic Technical Specifications



R30S



R45S



R60S

Single-phase induction motor (Watts)	550	950	1150
Brush speed (rpm)	650	650	650
Brush width (inches)	12	18	24
Clean water capacity (Gallons)	1.8	1.8	1.8
Dirty water capacity (Gallons)	.53	.66	.92
Water distribution		Gravity Feed	
Brush pressure (g/cm ²)	325	260	210
Weight (lbs)	52	68	75
Length (inches)	14.4	14.4	14.4
Width (inches)	15.9	21.5	27.8
Heights w/o handle (inches)	8.1	8.1	8.1
Height in operation	Adjustable handle ranges from 8.1 inches to 3.3 feet		
Hard floor coverage (up to ft ² /hr)	4628	7750	9580
Soft floor coverage (up to ft ² /hr)	1830	2906	4629
Retail Price	\$2,245	\$2,795	\$2,995