

Rotowash Flex

The stick handle enhances flexible working in tight areas.
An optional tank is available.

- A** Handle for left and right hand operation switches motor by tilting
- B** Easy grip water release control
- C** Pivoting quick release cable holder
- D** 10m mains cable
- G** Anodized aluminium handle, easy to stow
- H** Waste water tray lid with water level indicator
- I** Clean water tray
- K** Bowden controlled water distribution
- L** Coupling disconnects handle
- M** Brush pressure control knob
- P** Heavy duty side and front protector bumpers
- R** Easy to fit and remove brush axles
- S** Built-in brush location plate for simple and fast fitting of brushes
- T** Retractable transport rollers suspend load on brushes while not in operation
- U** Cylindrical brushes, easy to remove without using any tools. Available in multiple colours for hygiene control
- V** Easily removable waste water tray
- W** Safety thermal cut-out control
- X** Specially coated aluminium body housing for high mechanical resistance



Optional Accessories



Corner Brush

Clean tight corners easily.
Detaches when not needed.



Side Brush

Designed to reach the edges of all floors.



Universal Rotocart

Move the Rotowash to any location easily. Fits all machine models.

Rotowash Flex Technical Specifications



R20T



R30T



R45T

Single-phase induction motor (Watts)	400	550	950
Brush speed (rpm)	650	650	650
Brush width (inches)	10	12	18
Clean water capacity (Gallons)	.79	.79	.79
Dirty water capacity (Gallons)	.39	.53	.66
Water distribution		Gravity Feed	
Brush pressure (g/cm ²)	280	300	260
Weight (lbs)	35	47	62.8
Length (inches)	14.4	14.4	14.4
Width (inches)	11.9	15.9	21.5
Heights w/o handle (inches)	8.1	8.1	8.1
Height in operation	Adjustable handle ranges from 8.1 inches to 3.3 feet		
Hard floor coverage (up to ft ² /hr)	2475	4036	6997
Soft floor coverage (up to ft ² /hr)	1076	1615	2368
Retail Price	\$1,695	\$1,995	\$2,495